

This compact yet powerful 80W outdoor BUC harnesses advanced Gen III GaN technology, delivering exceptional broadband RF performance, high efficiency, and outstanding linearity and reliability for applications such as broadcast contribution and CBH

Key Features

- Built-in 1:1 Redundancy, no External Redundancy Controller required
- High Linearity, efficiency and MTBF
- Built-in High Precision true RMS Output Power Meter
- Built-in 110/220VAC power supply
- Web Interface, SNMP support
- Output Overdrive Protection
- Output VSWR Protection
- Thermal shutdown

Options

- Appendix 30B-15 (KL, 12.75-13.25GHz) and Kx (KX, 13.75-14.5GHz) bands
- Internal High-stability 10 MHz Reference
- 1U Rack mountable RCP (Remote Control Panel) for 1:1 redundancy



In addition to its exceptional performance and reliability, this device boasts a comprehensive suite of monitoring and control capabilities, easily accessible via Ethernet, serial RS232, RS485 interfaces, or dry contacts. It is the premier choice for demanding mobile and fixed applications, specifically designed for outdoor installations, and offers the advanced capability to utilize high MODCOD (up to 256 APSK) for broadcast contribution, as well as for Cellular Backhaul (CBH) and high-capacity data transmission for VSAT and SCPC User Terminals such as ESTELLA WaveSwitch modems that

combine both TDMA and dynamic SCPC waveforms in one modem. With an IP67 ingress protection rating, the device can be mounted outdoor under the direct sun rays on an antenna boom/kingpost, on the platform behind the antenna, or inside the antenna hub, effectively eliminating the W/G RF loss commonly associated with indoor units. Additionally, it does not require air-conditioning, resulting in significant reductions in the ongoing OPEX electrical costs and maintenance expenses, while eliminating the need for nearby shelter construction

MODELS		
RF CHARACTERISTICS	SBB0080KL	SBB0080KX
RF Frequency range	12.75 – 13.25 GHz	13.75 – 14.5 GHz / 14.0 – 14.5 GHz
IF Frequency range*	950-1525 MHz	950 - 1700 MHz / 950 – 1450 MHz
LO Frequency*	11.8 GHz	12.8 GHz / 13.05 GHz
RF CHARACTERISTICS		
P _{Sat} , Rated Output Power	49 dBm / 80 W	
P _{Lin1C} , Linear Power as defined by MIL-STD-188-164C, 1 carrier	47 dBm / 50 W	
P _{Lin2C} , Linear Power as defined by MIL-STD-188-164C, 2 carriers	46 dBm / 40 W	
Small Signal Gain	70 dB typ	
Gain Flatness over full frequency range	± 1.5 dB max	
Gain Flatness over any 40 MHz	± 0.4 dB max	
Gain Control	20 dB min dynamic range, 0.1 dB steps	
Gain Stability over full Temperature and Frequency ranges	± 1.5 dB max	
Gain stability over 24h at constant drive and temperature	±0.5 dB	
Linearity: IMD3, measured with 2 equal tones 5 MHz apart	-25 dBc at total power = P _{Lin2C}	
External Reference Frequency	10 MHz, sinusoidal, multiplexed with L-band (IF In)	
External Reference Level	0 dBm, ±5 dB	
External Reference SSB Phase Noise, max	-110 dBc/Hz @ 10 Hz; -140 dBc/Hz @ 1 kHz; -165 dBc/Hz @ 100 kHz;	-125 dBc/Hz @ 100 Hz; -155 dBc/Hz @ 10 kHz; -165 dBc/Hz @ 1 MHz;
Up-Converter SSB Phase Noise, max (not present if SSPA)	-50 dBc/Hz @ 10 Hz; -65 dBc/Hz @ 100 Hz; -80 dBc/Hz @ 1 kHz; -90 dBc/Hz @ 10 kHz; -100 dBc/Hz @ 100 kHz; -115 dBc/Hz @ 1 MHz	
Integrated Phase Noise	1° RMS max	
Output Spurious: In-band	< -60 dBc	
Out-of-band	Complies with ETSI EN 301 428/430 and MIL-STD188-164C	
Harmonics at P _{Lin2C}	< -60 dBc	
AM/PM Conversion	2.0°/dB max at P _{Lin1C}	
Noise Power Density	Tx < - 80 dBm/Hz Rx < - 145 dBm/Hz	
Output RF Power Monitor	-40 dB, 1dB peak-to-peak flatness over frequency range, calibration chart provided	
INTERFACES		ENVIRONMENTAL
IF Input connector	50 Ohms N-type (F)	Cooling systems
Input VSWR	1.5:1 max	Forced Air
RF Output Connector	WR75 grooved	Operating Temperature
Output VSWR	1.3:1 max	Storage
RF Sample	50 Ohms N-type (F)	
AC Power In	MS3102E16-10P	
M&C Interfaces: Ethernet, Serial RS-232 & RS-485, Form-C	MS3112E14-19P	
Redundancy	MS3112E14-19S	
POWER		MECHANICAL
AC Voltage Range	90-265 VAC	Dimensions (LxWxH)
Frequency Range	47-63 Hz	
Power Consumption at P _{Lin1C}	750 W	Weight
Power Consumption at P _{Lin2C}	650 W	